



ITEM	Hoshizaki Reach-in Refrigerator
MODEL	HRE-127MA-AHD
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.88kVA (3.70A)
AMPERAGE	Rated: 2.85A Starting: 12A
ELECTRIC CONSUMPTION	412W (Power Factor: 57%)(Except Drain Tank Heater 170W) Heater: 218W Defrost: 218W
HEAT REJECTION	610W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	1080L
OUTSIDE DIMENSIONS	1200mm(W) x 800mm(D) x 2015mm(H)
INSIDE DIMENSIONS	1096mm(W) x 626mm(D) x 1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Rear, Bottom)
INTERIOR	Stainless Steel, ABS Plastic(Door)
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Off Cycle
COMPRESSOR	Hermetic 270W (cooling capacity)
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R134a/240g
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -2 to 12°C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto-reset)
CASTER	Urethane (76mm DIA, 115mm HIGH)
SHELF	8 pcs.(Include Bottom Shelf)
WEIGHT	146kg (Gross 177kg)
PACKAGE	Carton (Wooden Pallet) 1260mm(W) x 900mm(D) x 2075mm(H)
OPERATING CONDITIONS	Ambient Temperature: 5 - 43°C Voltage Range: Rated Voltage ±6%

\*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.  
Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35°C.
3. The drain tank may overflow if the door is opened frequently or under highly humid conditions in the rainy or summer season.
4. Product Code: R263-C523

\*CUSTOMIZED  
BODY = SUS  
CASTER  
DRAIN TANK