



| | |
|--------------------------------|---|
| ITEM | Hoshizaki Reach-in Freezer |
| MODEL | HFE-70B-ALD-GN |
| POWER SUPPLY | 1 Phase 220 - 240V 50Hz Capacity: 1.04kVA (4.60A) |
| AMPERAGE | Rated: 3.57A Starting: 14.8A |
| ELECTRIC CONSUMPTION | 572W (Power Factor: 71%) (Except Drain Pan Heater 170W) Heater: 490W Defrost: 490W |
| HEAT REJECTION | 535W |
| POWER CORD | 2.3m (Plug with Earth Wire) |
| EFFECTIVE CAPACITY | 630L |
| OUTSIDE DIMENSIONS | 700mm(W) x 850mm(D) x 2015(-2045)mm(H) |
| INSIDE DIMENSIONS | 596mm(W) x 676mm(D) x 1484mm(H) |
| EXTERIOR | Stainless Steel, Galvanized Steel(Rear, Bottom) |
| INTERIOR | Stainless Steel |
| INSULATION | Polyurethane Foam |
| INSULATION FOAM BLOWING AGENT | Cyclopentane |
| DOOR | Full stainless steel doors external and interior |
| REFRIGERATION SYSTEM | Forced Air Circulation |
| DEFROST SYSTEM | Heater |
| COMPRESSOR | Hermetic 385W(Motor Size) |
| CONDENSER | Fin and Tube type, Air-cooled |
| EVAPORATOR | Fin and Tube type |
| REFRIGERANT | R404A/230g |
| TEMPERATURE CONTROL | Microprocessor (Digital Temp. Indication) Adjustable from -25 to -7°C |
| DEFROST CONTROL | Microprocessor |
| ELECTRIC CIRCUIT PROTECTION | Earth Wire, Circuit Breaker |
| REFRIGERANT CIRCUIT PROTECTION | Motor Protector (Auto-reset) |
| CASTER | Urethane (76mm DIA,115mm HIGH) |
| ACCESSORIES | SHELF 4 pcs. |
| WEIGHT | 130kg (Gross 152kg) |
| PACKAGE | Carton (Wooden Pallet) 760mm(W) x 950mm(D) x 2040mm(H) |
| OPERATING CONDITIONS | Ambient Temperature: 5 - 43°C Voltage Range: Rated Voltage ±6% |

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 43°C.
3. The drain tank may overflow if the door is opened frequently or under highly humid conditions in the rainy or summer season.
4. Product Code : R277-C713

SPECIFICATIONS
DRAIN TANK LONG DOOR
GN 2/1 DOOR LOCK
D850