







VIEW A(1/10)



PLUG



ITEM	Hoshizaki Undercounter Freezer
MODEL	FTE-170SDA-GN
POWER SUPPLY	1 Phase 220-240V 50Hz Capacity:0.95kVA(4.1A)
AMPERAGE	Rated 3.4A Starting 14.8A
ELECTRIC CONSUMPTION	Motor 510W(Power Factor65%) Heater 384W Refrigeration 569W Defrost 384W
HEAT REJECTION	900W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	412L
OUTSIDE DIMENSIONS	W1660×D700×H815mm
INSIDE DIMENSIONS	W1290×D527×H588mm
EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom)
INTERIOR	Stainless Steel, ABS Plastic
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
DOOR	Full stainless steel doors external and interior
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Glass Tube Heater
COMPRESSOR	Hermetic 110W
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube Type
REFRIGERANT	R134a/170g
TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -25 to -7℃
DEFROST CONTROL	Microprocessor controlled
ELECTRIC CIRCUIT PROTECTION	10A Fuse, Earth Wire
COMPRESSOR PROTECTION	Motor Protector
CASTER	Urethane (76mm DIA, 115mm HIGH)
SHELF	6pcs.
WEIGHT	Net:103kg (Gross: Approx. 115kg)
PACKAGE	Carton W1725×D780×H815mm
ACCESSORIES	Rail x 12
OPERATING CONDITIONS	Ambient Temperature:5-43℃ Voltage Range:Rated Voltage±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided.
Allow 10mm extra space at the installation site to meet any installation requirements(additional spacing is also required for proper air flow).
2. The heat rejection is based on the reached pull-down temperature at ambient temperature of 43℃ and power supply of 230V 50Hz.
The amperage and electric consumption are based on measurements at ambient temperature of 43℃ and power supply of 230V 50Hz.
3. The cabinet temperature range of -6 to 12℃ is guaranteed at ambient temperature of 30℃.
4. Product Code : T042-D008 (HLP)
*Customized
Caster with stopper H=115mm
Power Cord Australian 3 Pin Plug
GN1/2