


PRODUCT FEATURES

- Stainless steel interior and exterior.
- Programmable Digital controller and display.
- 6 x 1/1 Gastronorm adjustable shelves with rails
- Compact slide out refrigeration unit for quick maintenance.
- 2 years parts and labour warranty.
- Comes standard with 4 x 115mm lockable castors (not legs).
- Optional Adjustable legs 150 180mm (Sold separately).

TECHNICAL DRAWING





Exterior	Stainless Steel,
	Galvanized Steel (Rear /Bottom)
Interior	Stainless Steel
Max Storage Capacity	412L
Temperature Control	Microprocessor controlled Adjustable from
	-6 to 12°C
Condenser	Fin & Tube type, Air Cooled
Outside Dimensions	1660mm (W) x 700mm (D) x 815mm (H)
Inside Dimensions	1290mm (W) x 527mm (D) x 588mm (H)
Refrigeration System	Forced Air Circulation
Weight Net/Gross (kg)	103kg
AC Supply Voltage	1 PHASE 220 - 240V 50Hz
Amperage	Rated: 1.3A Starting: 6.8A
Refrigerant Charge	R134a/170g
Operating Conditions	Ambient Temp.: 5-43°C
	Voltage Range: Rated Voltage ±6%











