

# MFi REFRIGERATOR INCUBATOR




**NULINE**  
REFRIGERATION

Select from our new series of Refrigerated Incubators. Our MFi 70 is a premium stainless steel refrigerator equipped with a Microprocessor Controller with timing function, that offers a total control over the temperature of your items. The features of this model make it unique and suitable to satisfy your high standard needs.

## FEATURES

- Top Mounted System
- Cabinet Finish in Stainless Steel Interior/Exterior
- Automatic Defrost and Water Disposal
- 5 Adjustable Shelves per Door
- Available in Glass Door (TNG) or Solid Door (TN)
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 40°C
	700 L 1400 L
	740w x 830d x 2050h 1480w x 830d x 2050h

# MFi REFRIGERATOR INCUBATOR



MODEL	MFi70TN / G	MFi140TN / G
Gross Capacity	700 L	1400 L
External Dimensions in mm (w/d/h including castors or legs)	740 x 830 x 2050	1480 x 830 x 2050
Internal Dimensions in mm (w/d/h)	600 x 690 x 1475	1340 x 690 x 1475
Packed Dimensions in mm (w/d/h including pallet)	761 x 850 x 2100	1500 x 850 x 2100
Gross Weight – kg (packed weight)	134	225
Net Weight – kg	120	201
Voltage	240V	240V
Temperature Range	2°C to 40°C	2°C to 40°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C
Temperature Fluctuation	-/+ 1.5°C	-/+ 1.5°C
Refrigerant	R134a	R134a
Cooling System / Defrost	Fan Forced	Fan Forced
Exterior Cabinet Finish	Stainless Steel	Stainless Steel
Inner Liner Material	Stainless Steel	Stainless Steel
Door	Solid /Glass	Solid /Glass
Door Hinges	RH	LH / RH
Door Handle	Pull Handle	Pull Handle
Type of Controller	Digital / Microprocessor	Digital / Microprocessor
Temperature Display	External	External
Data Logger	Optional	Optional
Door Ajar Alarms	Optional	Optional
High and Low Readout	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Optional Optional	Optional Optional
Port Entry	Optional	Optional
Battery Back Up for Controller	Optional	Optional
Power Requirement	10amp GPO	10amp GPO
Castors	Yes	Yes
Adjustable Shelves	5	10
Usable Shelf Area in mm (w/d)	530 x 650	530 x 650
Light	LED	LED

Nuline Refrigeration reserves the right to alter the specifications without prior notice.