

ML SERIES VACCINE REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger Included
- Battery Backup for Controller
- Digital Display with Built in Alarms
- Hi / Lo Read Out
- Self Closing Door
- ARTG Number 269893



2°C to 8°C



29 L
59 L
125 L
300 L
400 L
500 L



445w x 458d x 535h
450w x 460d x 875h
595w x 610d x 840h
595w x 611d x 1560h
595w x 611d x 1820h
700w x 660d x 2020h



ML SERIES VACCINE REFRIGERATOR



Model	ML29GP	ML59GP	ML125GP/P
Gross Capacity	29 L	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	30	41	59
Net Weight - kg	27	38	55
Voltage	220V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Glass	Glass	Glass / Solid
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Included		
Door Ajar Alarms	Yes		
High and Low Readout	Visual / Audible		
BMS Connectivity (BMS Connectivity for Remote Alarms only) (BMS Connectivity for 4-20mA Transmitter)	Yes Optional		
Port Entry	Yes		
Battery Back-up for Controller	Yes		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm(w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		
Noise	45 dB(A)		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.

ML SERIES VACCINE REFRIGERATOR



Model	ML300GP/P	ML400GP/P	ML500GP/P
Gross Capacity	300 L	400 L	500 L
External Dimensions in mm (w/d/h including castors)	595 x 611 x 1560	495 x 611 x 1820	700 x 660 x 2020
Internal Dimensions in mm (w/d/h)	505 x 442 x 1345	505 x 422 x 1605	610 x 477 x 1735
Packed Dimensions in mm (w/d/h including pallet)	660 x 705 x 1630	660 x 705 x 1890	760 x 735 x 2100
Gross Weight - kg (packed weight)	77	87	132
Net Weight - kg	73	82	122
Voltage	220V		
Temperature Range	2°C to 8°C		
Ambient Temperature Range	10°C to 32°C		
Refrigerant	R600a		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	Enamelled Steel		
Inner Liner Material	ABS		
Door	Glass / Solid		
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Included		
Door Ajar Alarms	Yes		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Yes		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Yes		
Battery Back-up for Controller	Yes		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		Yes
Adjustable Shelves	7		
Usable Shelf Area in mm(w/d)	6 x 488 x 411	1 x 488 x 276	6 x 593 x 470 1 x 593 x 300
Light	LED		
Noise	45 dB(A)		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.