




MLB BREAST MILK REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger included
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Self-closing Doors



| | |
|---|--|
|  | 2°C to 4°C |
|  | 29 L 59 L 125 L |
|  | 445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h |

MLB BREAST MILK REFRIGERATOR



| Model | MLB29G | MLB59G | MLB125G |
|---|---------------------------|-----------------------------|-----------------------------|
| Gross Capacity | 29 L | 59 L | 125 L |
| External Dimensions in mm (w/d/h including castors) | 445 x 458 x 535 | 450 x 460 x 875 | 595 x 610 x 840 |
| Internal Dimensions in mm (w/d/h) | 361 x 205 x 400 | 390 x 300 x 720 | 505 x 442 x 625 |
| Packed Dimensions in mm (w/d/h including pallet) | 500 x 575 x 590 | 525 x 560 x 900 | 660 x 705 x 910 |
| Gross Weight - kg (packed weight) | 30 | 41 | 59 |
| Net Weight - kg | 27 | 38 | 55 |
| Voltage | 240V | | |
| Temperature Range | 2°C to 4°C | | |
| Ambient Temperature Range | 10°C to 32°C | | |
| Refrigerant | R600 | | |
| Cooling System / Defrost | Fan Forced / Automatic | | |
| Exterior Cabinet Finish | Enamelled Steel | | |
| Inner Liner Material | ABS | | |
| Door | Glass | | |
| Door Hinge | RH | | |
| Door Handle | Pull Handle | | |
| Type of Controller | Digital | | |
| Temperature Display | External | | |
| Data Logger | Included | | |
| Door Ajar Alarms | Yes | | |
| High and Low Readout | Visual / Audible | | |
| BMS Connectivity | | | |
| (BMS Connectivity for Remote Alarms only) | Yes | | |
| (BMS Connectivity for 4-20mA Transmitter) | Optional | | |
| Port Entry | Yes | | |
| Battery Back-up for Controller | Yes | | |
| Power Requirement | 10amp GPO | | |
| Watts | 125 | | |
| Castors | Adjustable Levelling Legs | | |
| Adjustable Shelves | 2 | 3 | 4 |
| Usable Shelf Area in mm(w/d) | 2 x 376 x 190 | 2 x 368 x 287 1 x 378 x 190 | 2 x 488 x 411 2 x 488 x 276 |
| Light | LED | | |

Nuline Refrigeration reserves the right to alter the specifications without prior notice.