




# MLi REFRIGERATOR INCUBATOR

**NULINE**  
REFRIGERATION

## FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Digital Display with Built-in Alarms
- Hi/Lo Readout



	2°C to 40°C
	29 L 59 L 125 L
	445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h



# MLi REFRIGERATOR INCUBATOR



Model	MLi29GP	MLi59GP	MLi125GP/P
Gross Capacity	29	59 L	125 L
External Dimensions in mm (w/d/h including castors)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 300 x 720	505 x 442 x 625
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	525 x 560 x 900	660 x 705 x 910
Gross Weight - kg (packed weight)	30	41	59
Net Weight - kg	27	38	55
Voltage	220V		240V
Temperature Range	2°C to 40°C		
Ambient Temperature Range	10°C to 32°C		
Temperature Fluctuation	±1°C		
Refrigerant	R600		
Cooling System / Defrost	Fan Forced / Automatic		
Exterior Cabinet Finish	White Enamel		
Inner Liner Material	ABS		
Door	Glass	Glass	Glass / Solid
Door Hinge	RH		
Door Handle	Pull Handle		
Type of Controller	Digital		
Temperature Display	External		
Data Logger	Optional		
Door Ajar Alarms	Yes		
High and Low Readout	Visual / Audible		
BMS Connectivity			
(BMS Connectivity for Remote Alarms only)	Yes		
(BMS Connectivity for 4-20mA Transmitter)	Optional		
Port Entry	Yes		
Battery Back-up for Controller	N/A		
Power Requirement	10amp GPO		
Castors	Adjustable Levelling Legs		
Adjustable Shelves	2	3	4
Usable Shelf Area in mm(w/d)	2 x 376 x 190	2 x 368 x 287 1 x 378 x 190	2 x 488 x 411 2 x 488 x 276
Light	LED		
Noise	45 dB(A)		

Nuline Refrigeration reserves the right to alter the specifications without prior notice.